

# LED Gridlight (Triple) 54w

High Luminosity LEDs



LED Gridlight - EFX18x3WTGL

## LED Gridlight 18w - EFX-18x3WTGL

The Eco-FX LED Gridlight offers high luminosity giving efficient heat dissipation (surface temperature 55°C, junction temperature 65°C). The long life driver offers constant current and voltage. Offering total flexibility in the retail environment.

Product Code	EFX-18x3WTGL
Size	360mm x 145mm
Beam Angle	45°
Input Voltage	110-265Vac
Frequency	50/60 Hz
Transformer Output	54W
Running Current	2100mA
Power Factor	0.9
Chip Set	Cree XR-E
Efficiency (LOR)	92%
Colour Temperature	Warm White 2700k    Cool White 6000-6500k
Lumen	Warm White 2430lm    Cool White 3240lm
Efficacy	Warm White 45 lm/w    Cool White 60 lm/w
CRI	Warm White >80    Cool White >75
Internal Temperature	65°
External Temperature (Front)	55°
External Temperature (Back)	60°
Operating Temperature	-20° / +45°
IP Rating	20

### Technical 54w

Product Code	EFX-18x3WTGL
Size	360mm x 145mm
Beam Angle	45°
Input Voltage	110-265Vac
Frequency	50/60 Hz
Transformer Output	54W
Running Current	2100mA
Power Factor	0.9
Chip Set	Cree XR-E
Efficiency (LOR)	92%
Colour Temperature	Warm White 2700k    Cool White 6000-6500k
Lumen	Warm White 2430lm    Cool White 3240lm
Efficacy	Warm White 45 lm/w    Cool White 60 lm/w
CRI	Warm White >80    Cool White >75
Internal Temperature	65°
External Temperature (Front)	55°
External Temperature (Back)	60°
Operating Temperature	-20° / +45°
IP Rating	20

