

# LED Downlight 12w

Multi-purpose LED Light Fitting



LED Downlight - EFX-12WDL

Technical 12w	
Product Code	EFX-12WDL
Size	Ø90mm x 120mm
Beam Angle	40°
Input Voltage	110-265Vac
Frequency	50/60 Hz
Transformer Output	12W
Running Current	650mA
Power Factor	0.8
Chip Set	Epistar
Efficiency (LOR)	95%
Colour Temperature	Warm White 2700-3300k Pure White 3800-4600k Cool White 5500-6500k
Lumen	Warm White 650lm Pure White 680lm Cool White 720lm
Efficacy	Warm White 54.1 lm/w Pure White 56.7 lm/w Cool White 60 lm/w
CRI	Warm White >80 Pure White >75 Cool White >70
Internal Temperature	65°
External Temperature (Front)	50°
External Temperature (Back)	55°
Operating Temperature	-40° / +50°
IP Rating	20

## LED Downlight 12w - EFX-12WDL

The Eco-FX LED Downlight is available in various LED configurations and wattages. We also produce a dimmable version. Available in black, white and aluminium.



**EPISTAR** **RoHS**

### Eco-FX Limited

Office 1, 192 Shoreham Street  
Sheffield S1 4SQ, UK

t: +44 (0) 114 321 9610  
e: enquiries@eco-fx.co.uk

w: www.eco-fx.co.uk

Issue April 2012

©Copyright 2012 - Eco-FX Limited