

LED Floodlight 50w



LED Floodlight – EFX-XTLFL50W


LED Floodlight – EFX-XTLFL50W

The 50W Flood Light consists of the highest quality components available in today's technology, making it the ultimate lighting solution for any high power application.

- Return on investment can be achieved within 1 year of operation, compared to a Halogen lamp.
- Highly energy efficient technology achieving a rating of 95.
- Light and compact design for easy and safe installation.

Applications

- Outdoor Fields
- Building Exteriors
- Golf Courses
- Train Stations
- Factories/Warehouses
- Car Parks
- Ports
- Sporting Arenas
- Sports Courts/Stadiums
- Airports



Eco-FX Limited

Office 1, 192 Shoreham Street
Sheffield S1 4SQ, UK

t: +44 (0) 114 321 9610
e: enquiries@eco-fx.co.uk

w: www.eco-fx.co.uk

Technical

Product Code	EFX-XTLFL50W
Size	235mm x 280mm x 70mm
Beam Angle	120°
Input Voltage	110-265Vac
Frequency	50/60 Hz
Transformer Output	51.6w
Running Current	330mA
Power Factor	0.95
Chip Set	Bridgelux
Efficiency (LOR)	95%
Colour Temperature	Cool White 6000k
Lumen	Cool White 4725lm
Efficacy	91.57lm/w
CRI	Cool White >80
LED Life	30,000Hrs
Operating Temperature	-20° / +50°
IP Rating	65

