

# LED High Bay 80W



LED High Bay - EFX-GLHBPC80W

## LED High Bay - EFX-GLHBPC80W

The Eco-FX LED High Bay range is available in various LED configurations and wattages. The 80W High Bay consists of the highest quality components available in today's technology, making it the ultimate lighting solution for any high power application.

The Body has a steel heat sink for fast dissipation of heat from the LEDs, complete with a polycarbonate refractor for 360° light coverage

- Return on investment can be achieved within 1 year of operation, compared to a Halogen lamp.
- Highly energy efficient technology achieving a rating of 95

Product Code	EFX-GLHBPC80W
Size	Ø420mm x 462mm
Beam Angle	360°
Input Voltage	110-265Vac
Frequency	50/60 Hz
Transformer Output	80W
Running Current	0.56A
Power Factor	0.9
Chip Set	BRIDGELUX
Efficiency (LOR)	95%
Colour Temperature	Cool White 5000k
Lumen	Cool White 7180lm
Efficacy	Cool White 89.75lm/w
CRI	Cool White >80
LED Life	50,000Hrs
Operating Temperature	-20° / +40°
IP Rating	20

## Technical

Product Code	EFX-GLHBPC80W
Size	Ø420mm x 462mm
Beam Angle	360°
Input Voltage	110-265Vac
Frequency	50/60 Hz
Transformer Output	80W
Running Current	0.56A
Power Factor	0.9
Chip Set	BRIDGELUX
Efficiency (LOR)	95%
Colour Temperature	Cool White 5000k
Lumen	Cool White 7180lm
Efficacy	Cool White 89.75lm/w
CRI	Cool White >80
LED Life	50,000Hrs
Operating Temperature	-20° / +40°
IP Rating	20

